

1. PRODUCT & COMPANY IDENTIFICATION

1. PRODUCT & COMPANY IDENTIFICATION		NZ DISTRIBUTOR Steve's Wholesale Ltd. Units 5 - 7 / 408 The Esplanade Island Bay Wellington 6023 team@steveswholesale.nz Emergency Contact: Steve Collings 0800 303 303 0274 905 708 Poison Control 0800 POISON (0800 764 766)
1.1	Product Name:	BIRCHWOOD CASEY FLAT BLACK
1.2	Chemical Name:	Paint BC15112
1.3	Synonyms:	NA
1.4	Trade Names:	Birchwood Casey Flat Black
1.5	Product Uses & Restrictions:	Lubricant
1.6	Distributor's Name:	Birchwood Casey
1.7	Distributor's Address:	7887 Fuller Road, Suite #100, Eden Prairie, MN 55344 USA
1.8	Emergency Phone:	ChemTrec +1 (800) 424-9300 / +1 (703) 527-3887 or Poison Control Center +1 (866) 291-7152
1.9	Business Phone / Fax:	+1 (952) 388-6717

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).</p> <p>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.</p> <p><u>Classification:</u> Flam. Liq.2; Repr. 2; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2</p> <p><u>Hazard Statements (H):</u> H225 – Highly flammable liquid and vapor. H361 – Suspected of damaging fertility or the unborn child. H317 – May cause an allergic skin reaction. H320 – Causes eye irritation.</p> <p><u>Precautionary Statements (P):</u> P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing vapors. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P302+P352 – IF ON SKIN - Wash with soap and water. P305+P351+P338 – IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs - Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 - In case of fire, CO₂, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P405 – Store locked up. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	
-----	------------------------	--	--


3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ppm	ppm	ppm	PEL	STEL	IDLH		
TOLUENE	108-88-3	XS52500000	203-625-9	NA	50	300	100	150	574	200	300	500	SKIN	
	Flam. Liq. 2; Repr. 2; Asp. Tox. 1; STOT RE 2 *; Skin Irrit. 2; STOT SE 3; H225, H361d ***, H304, H373 **, H315, H336													
METHYL ETHYL KETONE	78-93-3	EL6475000	201-159-0	NA	200	300	150	445	NF	200	300	3000		
	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336													
ETHYL ACETATE	141-78-6	AH5425000	205-500-4	NA	400	400	200	400	NF	NA	NA	2000	400 TWA	
	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336													
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	NA	1000	1900	1880	NF	NF	1000	1900	3300		
	Flammable Liquids 2; H225													
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	UB7700000	203-539-1	NA	100	150	100	NF	NF	100	150	NA		
	Flam. Liq. 3; STOT SE 3; H226, H336													
BUTYL ACETATE	123-86-4	AF73500000	204-658-1	NA	150	200	150	200	NF	200	200	1700	150 TWA	
	Flam. Liq. 3; Acute Tox. 5; Skin Irrit. 2; Eye Irrit. 2A; STOT-SE 3; Acute Aq. 3; Chron. Aq. 3; H226, H315, H319, H333, H336, H412													
AMORPHOUS SILICA	7631-86-9	VV7565000	231-545-4	NA	(10)	NA	NF	NF	NF	(6)	NA	NA		
	Eye Irrit. 2A; STOT SE 3; H319, H335													
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	NA	400	500	400	500	NF	400	500	2000	400 TWA	
	Flam. Liq. 2; Skin Irrit. 3; Eye Irrit. 2A; STOT SE 3; H225, H316, H319													
ETHYL 3-ETHOXYPROPIONATE	763-69-9	UF3325000	212-112-9	NA	NA	NA	NF	NF	NF	NA	NA	NA		
	Flam. Liq. 3; Aquatic Chronic 3; H226, H412													
CARBON BLACK	1333-86-4	FF5800000	215-609-9	NA	(3.5)	NA	(3.5)	NF	NF	(3.5)	NA	NA		
TITANIUM DIOXIDE	13463-67-7	XR2275000	236-675-5	NA	(10)	NA	NF	NF	NF	(3)	NA	5000		

4. FIRST AID MEASURES

4.1	First Aid:	<p>Ingestion: DO NOT INDUCE VOMITING. Contact Poison Control Center +1 (866) 291-7152 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p>Eyes: If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p>Skin: Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p>Inhalation: Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>											
4.2	Effects of Exposure:	<p>Ingestion: If product is swallowed, may cause nausea, temporary gastrointestinal irritation. Vomiting and/or diarrhea.</p> <p>Eyes: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: None expected.</p>											
4.3	Symptoms of Overexposure:	<p>Ingestion: Nausea, intestinal discomfort, vomiting and/or diarrhea.</p> <p>Eyes: Overexposure in eyes may cause redness, itching and watering.</p> <p>Skin: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals.</p>											
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.											
4.5	Chronic Health Effects:	None reported by the manufacturer.											
4.6	Target Organs:	Eyes, Skin, Liver, Kidney, CNS											
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes).	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: #FF0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: #FFA500; color: white;">PHYSICAL HAZARDS</td> <td style="text-align: center;">0</td> </tr> <tr> <td colspan="2" style="background-color: #000000; color: white;">PROTECTIVE EQUIPMENT</td> </tr> <tr> <td style="background-color: #000000; color: white;">EYES</td> <td style="background-color: #000000; color: white;">SKIN</td> </tr> </table>	HEALTH	2	FLAMMABILITY	3	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT		EYES	SKIN
HEALTH	2												
FLAMMABILITY	3												
PHYSICAL HAZARDS	0												
PROTECTIVE EQUIPMENT													
EYES	SKIN												

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	<p>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Fine mist or sprays may be flammable at temperatures below the flashpoint. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO₂, NO_x).</p>	
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical. Use water spray to cool unopened containers.	
5.3	Firefighting Procedures:	<p>This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.</p> <p>First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.</p>	



6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	ACGIH		NOHSC			OSHA			OTHER
		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
	CHEMICAL NAME(S)									
	TOLUENE	50	300	100	150	574	200	300	500	SKIN
	METHYL ETHYL KETONE	200	300	150	445	NF	200	300	3000	
	ETHYL ACETATE	400	400	200	400	NF	NA	NA	2000	400 TWA
	ETHANOL (SD ALCOHOL 40B)	1000	1900	1880	NF	NF	1000	1900	3300	
	PROPYLENE GLYCOL MONOMETHYL ETHER	100	150	100	NF	NF	100	150	NA	
	BUTYL ACETATE	150	200	150	200	NF	200	200	1700	150 TWA
	SILICA	(10)	NA	NF	NF	NF	(6)	NA	NA	
	ISOPROPYL ALCOHOL	400	500	400	500	NF	400	500	2000	400 TWA
	CARBON BLACK	(3.5)	NA	(3.5)	NF	NF	(3.5)	NA	NA	
	CI 77891 (TITANIUM DIOXIDE)	(10)	NA	NF	NF	NF	(3)	NA	5000	
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.								
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.								
8.4	Eye Protection:	Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166.								
8.5	Hand Protection:	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.								
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.								

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Black liquid
9.2	Odor:	Solvent odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	72-172 °C (163-342 °F)
9.7	Flashpoint:	2.2 °C (36 °F) PMCC
9.8	Upper/Lower Flammability Limits:	LEL 1.0% / UEL 19.0%
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	Heavier than air
9.11	Relative Density:	0.94
9.12	Solubility:	Immiscible
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC: 79 % by volume; 679 g/L (5.67 lb/gal). Evaporation rate: slower than ether



SAFETY DATA SHEET

Page 4 of 7
BC-017

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4/14/2015

10. STABILITY & REACTIVITY

10.1	Stability:	Relatively stable under ambient conditions when stored properly.
10.2	Hazardous Decomposition Products:	If exposed to <u>extremely high temperatures</u> , products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is not presented in this document.		
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.		
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).		
11.5	Suspected Carcinogen:	<u>Toluene</u> : IARC Group 3 (not classifiable as to its carcinogenicity to humans). <u>Carbon Black</u> : IARC listed 2B (possible human carcinogen); ACGIH – A4 Not classifiable as a human carcinogen <u>Ethyl Acetate</u> : IARC Group 3 (not classifiable as to its carcinogenicity to humans).		
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: <u>Ethyl Acetate</u> : $K_{OC} = 0.73$. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Butyl Acetate</u> : $K_{OC} = 1.82$. Water solubility: 120 parts H ₂ O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Isopropyl Alcohol</u> : $\log K_{OW} = 0.05-0.14$. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY, IP ≤ 1.0 L)	
14.3	IMDG (OCN):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1263, PINTURA MATERIAL RELACIONADO, 3, II, (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	


* This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)

15. REGULATORY INFORMATION

HSR002663


15.1	SARA Reporting Requirements:	This product contains <u>Toluene</u> , <u>Methyl Ethyl Ketone</u> , <u>Propylene Glycol Monomethyl Ether</u> and <u>Isopropyl Alcohol</u> substances subject to SARA Title III, Section 313 reporting requirements. This product contains <u>Ethyl Acetate</u> and <u>Butyl Acetate</u> substance that is subject to SARA Title III, section 304 reporting.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	<u>Toluene</u> : 454 kg (1,000 lbs.); <u>Ethyl Acetate</u> : 2,270 kg (5,000 lbs); <u>Butyl Acetate</u> : 2,270 kg (5,000 lbs)	
15.5	Other Federal Requirements:	NA	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable, Other Toxic Effects).	
15.7	State Regulatory Information:	<p><u>Toluene</u> is found on the following state criteria lists: California Proposition 65, FL, MA, MN, PA, WA, and WI.</p> <p><u>Methyl Ethyl Ketone</u> is found on the following state criteria list: FL, MA, MN, NJ PA WA and WI.</p> <p><u>Ethyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, WA, and Wisconsin Hazardous Substances List (WI).</p> <p><u>Ethanol</u> is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA.</p> <p><u>Propylene Glycol Monomethyl Ether</u> is found on the following state criteria lists: FL, MA, MN, PA and WA.</p> <p><u>Butyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA and WA.</p> <p><u>Isopropyl Alcohol</u> is found on the following state criteria lists: FL, MA, MN, NJ, PA, and WA.</p> <p><u>Carbon Black</u> is listed in the following state criteria lists: California Proposition 65 (CA65), MA, MN, NJ, and PA</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p> <p>WARNING: This product contains <u>Toluene</u> and <u>Carbon Black</u>, chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires this warning be given to customers in the State of California.</p>	

15. REGULATORY INFORMATION – cont'd

15.8	Other Requirements:	<p>The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC:</p> <p><u>Toluene</u>: Flammable (F), Harmful (Xn). <u>Risk Phrases</u> (R): 11-38-48/20-63-65-67 – Highly flammable. Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness. <u>Safety Phrases</u> (S): (2-)36/37-62 – Keep out of reach of children. Wear suitable protective clothing and gloves. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label where possible.</p> <p><u>Methyl Ethyl Ketone</u>: Flammable (F), Irritant (Xi). <u>Risk Phrases</u> (R): 11-36-66-67 – Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. <u>Safety Phrases</u> (S): 2-9-16 – Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking.</p> <p><u>Ethanol</u>: Flammable (F) <u>Risk Phrases</u> (R): 11 – Highly flammable. <u>Safety Phrases</u> (S): (2-)7-16 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking.</p> <p><u>Butyl Acetate</u>: Flammable (F) <u>Risk Phrases</u> (R): 10-66-67 – Flammable. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. <u>Safety Phrases</u> (S): (2-)25 – Keep out of reach of children. Avoid contact with eyes.</p> <p><u>Isopropyl Alcohol</u>: Flammable (F), Irritant (Xi). <u>Risk Phrases</u> (R): 11-36-67 – Highly flammable. Irritating to eyes. Vapors may cause drowsiness or dizziness. <u>Safety Phrases</u> (S): (2-)7-16-24/25-26 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</p>	
------	---------------------	--	---

16. OTHER INFORMATION

SW Revised 01.12.2020

16.1	Other Information:	<p>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing vapors. Wash exposed skin areas thoroughly with soap and water after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. For specific first aid treatment (see section 4 of this Safety Data Sheet). Wash contaminated clothing before reuse. In case of fire, CO₂, Halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. Store locked up. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.</p> <p>WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Birchwood Casey's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Birchwood Casey 7887 Fuller Road, Suite #100 Eden Prairie, MN 55344 USA Tel: +1 (952) 388-6701 Fax: +1 (952) 388/6702 http://www.birchwoodCasey.com	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₀₁ or TC, TC₀₁, LC₀₁, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment