



# SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards      SDS Revision: 2.1      SDS Revision Date: 10/25/2018

## 1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	<b>GUN STOCK SEALER AND FILLER</b>	NZ DISTRIBUTOR Steve's Wholesale Ltd. Units 5 – 7 / 408 The Esplanade Island Bay Wellington 6023
1.2	Chemical Name:	Alkyd Resin Solution	team@steveswholesale.nz
1.3	Synonyms:	23323	Emergency Contact: Steve Collings 0800 303 303
1.4	Trade Names:	Gun Stock Sealer And Filler	0274 905 708
1.5	Product Use:	Sealer & Filler	Poison Control 0800 POISON (0800 764 766)
1.6	Distributor's Name:	Birchwood Casey, LLC	
1.7	Distributor's Address:	3260 Winpark Drive, New Hope, MN., 55427 USA	
1.8	Emergency Phone:	<b>ChemTrec +1 (800) 424-9300 / +1 (703) 527-3887 or Poison Control Center +1 (866) 291-7152</b>	
1.9	Business Phone / Fax:	+1 (952) 388-6717	

## 2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).</p> <p><b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.</b></p> <p>Classification: Flam. Liq.2; Repr. 2; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2</p>	
2.2	Label Elements:	<p><b>Hazard Statements (H):</b> H225 – Highly flammable liquid and vapor. H361 – Suspected of damaging fertility or the unborn child. H317 – May cause an allergic skin reaction. H320 – Causes eye irritation.</p> <p><b>Precautionary Statements (P):</b> P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing vapors. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do NOT induce vomiting. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs - Get medical advice/attention. P321 – For specific first aid treatment (See Section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 - In case of fire, CO<sub>2</sub>, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P405 – Store locked up. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	
2.3	Other Warnings:	<p><b>WARNING!</b> This product can expose you to chemicals including Toluene which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>. In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. Keep out of reach of children.</p>	

## 3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m <sup>3</sup> )									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ppm	ppm	ppm	PEL	STEL	IDLH		
MODIFIED ALKYL RESIN	NA	NA	NA	30-60	NA	NA	NF	NF	NF	NA	NA	NA		
VM & P NAPHTHA	8030-30-6	DE3030000	232-443-2	15-40	400	NA	NF	NF	NF	100	NA	1000		
	Carc. 1B; Muta. 1B; Asp. 1; H350, H340, H304													
XYLENE	1330-20-7	ZE2100000	215-535-7	15-40	100	150	(80)	350	NF	100	150	900		
	Flam. Liq. 3, Acute Tox 4, Skin Irrit. 2, Acute Tox. 4; H226, H312, H315, H332													
STODDARD SOLVENT	64742-47-8	OA5504000	265-149-8	15-40	NA	NA	NF	NF	NF	(5)	NA	NA		
	Asp. Tox. 1; H304													
VINYL TOLUENE	25013-15-4	WL5075000	246-562-2	1-3	50	100	(50)	242	NF	100	NA	400		
	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; Asp. Tox. 1; Aquatic Ac. 2; H226, H304, H315, H319, H332, H335, H401													
TOLUENE	108-88-3	XS5250000	203-625-9	1-3	50	300	100	150	574	200	300	500	SKIN	
	Flam. Liq. 2; Repr. 2; Asp. 1; STOT RE 2*; Skin Irrit. 2; STOT SE 3; H225, H361d***, H304, H373**, H315, H336													

## 4. FIRST AID MEASURES

4.1	First Aid:	<p><b>Ingestion:</b> DO NOT INDUCE VOMITING. Contact Poison Control Center +1 (866) 291-7152 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p><b>Eyes:</b> If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p><b>Skin:</b> Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p><b>Inhalation:</b> Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>													
4.2	Effects of Exposure:	<p><b>Ingestion:</b> Irritation to the gastrointestinal tract. This material can enter the lungs during swallowing or vomiting and cause lung damage.</p> <p><b>Eyes:</b> Irritation upon direct contact. Symptoms may include stinging, tearing, redness and swelling.</p> <p><b>Skin:</b> Mildly irritating. Prolonged or repeated skin contact can result in defatting, drying of the skin with symptoms of redness, stinging. May be absorbed through the skin in harmful amounts.</p> <p><b>Inhalation:</b> Inhalation may cause irritation to the respiratory tract (nose, throat and lungs). Inhalation of high vapor concentrations may cause central nervous system effects, and symptoms such as headache, dizziness, disorientation.</p>													
4.3	Symptoms of Overexposure:	<p><b>Ingestion:</b> Nausea, intestinal discomfort, vomiting and/or diarrhea.</p> <p><b>Eyes:</b> Overexposure in eyes may cause redness, itching and watering.</p> <p><b>Skin:</b> Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals.</p>													
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.													
4.5	Chronic Health Effects:	None reported by the manufacturer.													
4.6	Target Organs:	Eyes, Skin, Lungs, Liver, Kidney, CNS													
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing skin, eye, respiratory, CNS, bone-marrow disorders, liver or kidney disease.	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>2</b></td> </tr> <tr> <td style="background-color: #FF0000; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>3</b></td> </tr> <tr> <td style="background-color: #FFA500; color: white;"><b>PHYSICAL HAZARDS</b></td> <td style="text-align: center;"><b>0</b></td> </tr> <tr> <td colspan="2" style="background-color: #000000; color: white;"><b>PROTECTIVE EQUIPMENT</b></td> </tr> <tr> <td style="background-color: #000000; color: white;"><b>EYES</b></td> <td style="background-color: #000000; color: white;"><b>SKIN</b></td> </tr> <tr> <td style="background-color: #000000; color: white;"><b>LUNGS</b></td> <td style="background-color: #000000; color: white;"><b>B</b></td> </tr> </table>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>3</b>	<b>PHYSICAL HAZARDS</b>	<b>0</b>	<b>PROTECTIVE EQUIPMENT</b>		<b>EYES</b>	<b>SKIN</b>	<b>LUNGS</b>	<b>B</b>
<b>HEALTH</b>	<b>2</b>														
<b>FLAMMABILITY</b>	<b>3</b>														
<b>PHYSICAL HAZARDS</b>	<b>0</b>														
<b>PROTECTIVE EQUIPMENT</b>															
<b>EYES</b>	<b>SKIN</b>														
<b>LUNGS</b>	<b>B</b>														

## 5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	<p><b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR!</b> Keep away from heat, lit cigarettes, sparks &amp; open flame. Keep container closed. This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Fine mist or sprays may be flammable at temperatures below the flashpoint. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO<sub>2</sub>, NO<sub>x</sub>).</p>	
5.2	Extinguishing Methods:	Water, Foam, CO <sub>2</sub> , Dry Chemical. Use water spray to cool unopened containers.	
5.3	Firefighting Procedures:	<p>This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.</p> <p>First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.</p>	


## 6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., &lt; 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use <b>ONLY</b> non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	--

## 7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

## 8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m <sup>3</sup> )	ACGIH	NOHSC			OSHA			OTHER			
		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH			
		<b>CHEMICAL NAME(S)</b>										
		TOLUENE		50	300	100	150	574	200	300	500	SKIN
		VM & P NAPHTHA		400	NA	NF	NF	NF	100	NA	1000	
		XYLENE		100	150	(80)	350	NF	100	150	900	
STODDARD SOLVENT		NA	NA	NF	NF	NF	(5)	NA	NA			
VINYL TOLUENE		50	100	(50)	242	NF	100	NA	400			
8.2	Ventilation & Engineering Controls:	Use general/dilution or local exhaust ventilation as needed to ensure that occupational exposure limits are not exceeded. Do not use in enclosed spaces. When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.										
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.										
8.4	Eye Protection:	Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166.										
8.5	Hand Protection:	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.										
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.										

## 9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Clear amber liquid
9.2	Odor:	Aromatic odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	116.1 °C (241 °F)
9.7	Flashpoint:	15.6 °C (60 °F) Setflash
9.8	Upper/Lower Flammability Limits:	LEL 1.0% / UEL 19.0%
9.9	Vapor Pressure:	17 mm Hg
9.10	Vapor Density:	3.9
9.11	Relative Density:	0.87
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log P <sub>ow</sub> ):	NA



# SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards      SDS Revision: 2.1      SDS Revision Date: 10/25/2018

## 9. PHYSICAL & CHEMICAL PROPERTIES – cont'd

9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	VOC: 100% by volume; Evaporation Rate: 1.7

## 10. STABILITY & REACTIVITY

10.1	Stability:	Relatively stable under ambient conditions when stored properly.
10.2	Hazardous Decomposition Products:	If exposed to <b>extremely high temperatures</b> , products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids.

## 11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: <u>Toluene</u> : LD <sub>50</sub> (oral, rat): 636 mg/kg; <u>Xylene</u> : LD <sub>50</sub> (oral, rat): 636 mg/kg		
11.3	Acute Toxicity:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.		
11.4	Chronic Toxicity:	This material may aggravate any pre-existing skin condition (e.g., dermatitis).		
11.5	Suspected Carcinogen:	<u>Toluene</u> and <u>Xylene</u> : IARC Group 3 (not classifiable as to its carcinogenicity to humans).		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans. There is ample evidence that <u>Xylene</u> produces embryotoxicity and fetotoxicity in mice and rats, but xylene is not considered teratogenic.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

## 12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There are no specific data available for this product.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

## 13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)

## 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1866, RESIN SOLUTION, 3, II, (LTD QTY, IP ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR)*:	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1866, RESIN SOLUTION, 3, II (LTD QTY, IP ≤ 0.50 L)	
14.3	IMDG (OCN):	UN1866, RESIN SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1866, RESIN SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1866, RESIN SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	



# SAFETY DATA SHEET

Page 5 of 7  
BC-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 10/25/2018

## 14. TRANSPORTATION INFORMATION – cont'd

14.6	SCT (MEXICO):	UN1866, SOLUCIONES DE RESINA, 3, II, (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1866, RESIN SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.8	EXCEPTED QUANTITY	This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)	

## 15. REGULATORY INFORMATION

HSR002662

15.1	SARA Reporting Requirements:	This product contains <u>Toluene</u> , <u>Vinyl Toluene</u> and <u>Xylene</u> , substances subject to SARA Title III, Section 313 reporting requirements.	
15.2	SARA TPQ:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity:	<u>Toluene</u> : 454 kg (1,000 lbs); <u>Xylene</u> : 454 kg (1,000 lbs)	
15.5	Other Federal Requirements:	NA	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable, Other Toxic Effects).	
15.7	State Regulatory Information:	<p><u>Toluene</u> is found on the following state criteria lists: California Proposition 65, FL, MA, MN, PA, WA, and WI.</p> <p><u>Xylene</u> is found on the following state criteria list: FL, MA, MI, MN, NJ, PA, WA and WI.</p> <p><u>VM &amp; P Naphtha</u> is found on the following state criteria lists: FL, MA, MN, PA and WA.</p> <p><u>Vinyl Toluene</u> is found on the following state criteria lists: FL, MA, MN, PA and WA.</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p> <p><b>WARNING:</b> This product contains <u>Toluene</u>, a substance known to the State of California to cause birth defects or other reproductive harm.</p>	
15.8	Other Requirements:	<p> <b>WARNING:</b> This product can expose you to chemicals including Toluene which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>. California law requires this warning be given to customers in the State of California.</p>	



# SAFETY DATA SHEET




Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 10/25/2018

## 16. OTHER INFORMATION

SW revised 30.12.2020

16.1	Other Information:	<p><b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.</b> Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing vapors. Wash exposed skin areas thoroughly with soap and water after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. <b>IF SWALLOWED:</b> Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. <b>IF ON SKIN -</b> Wash with soap and water. <b>IF IN EYES:</b> Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. For specific first aid treatment (see section 4 of this Safety Data Sheet). Wash contaminated clothing before reuse. In case of fire, CO<sub>2</sub>, Halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. Store locked up.</p> <p><b>KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.</b></p> <p><b>WARNING:</b> This product can expose you to chemicals including Toluene and which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to  <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Birchwood Casey, LLC knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	<p><b>Birchwood Casey, LLC</b>  3260 Winpark Drive  New Hope, MN 55427 USA  Tel: +1 (952) 388-6717  Email: <a href="mailto:customerservice@birchwoodcasey.com">customerservice@birchwoodcasey.com</a>  <a href="http://www.birchwoodCasey.com">http://www.birchwoodCasey.com</a></p>	
16.5	Prepared by:	<p><b>ShipMate, Inc.</b>  P.O. Box 787  Sisters, Oregon 97759-0787 USA  Tel: +1 (310) 370-3600  Fax: +1 (310) 370-5700  <a href="http://www.shipmate.com">http://www.shipmate.com</a></p>	





# SAFETY DATA SHEET

Page 7 of 7  
BC-021

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 10/25/2018

## DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

### GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

### EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

### HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

<b>HEALTH</b>
<b>FLAMMABILITY</b>
<b>PHYSICAL HAZARDS</b>
<b>PERSONAL PROTECTION</b>

### PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

### OTHER STANDARD ABBREVIATIONS:


Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity - Repeat Exposure
STOT SE	Specific Target Organ Toxicity - Single Exposure

### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

<b>FLAMMABILITY LIMITS IN AIR:</b>	
<b>Autoignition Temperature</b>	Minimum temperature required to initiate combustion in air with no other source of ignition
<b>LEL</b>	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
<b>UEL</b>	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

### HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>10</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>10</sub> , LD <sub>10</sub> , & LD <sub>01</sub> or TC, TC <sub>01</sub> , LC <sub>10</sub> , & LC <sub>01</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>OW</sub> or log K <sub>OC</sub>	Coefficient of Oil/Water Distribution

### REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment