### **Safety Data Sheet**



## Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • Gun Stock Wax

Product Code 23723

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified use(s)** • Protects firearm stocks from weather and handling by removing imperfections

1.3 Details of the supplier of the safety data sheet

NZ DISTRIBUTOR

Manufacturer

Birchwood Casey, LLC

Steve's Wholesale Ltd. Units 5 – 7 / 408
The Esplanade

7887 Fuller Road, Suite 100
Eden Prairie, MN 55344
Island Bay Wellington 6023

United States team@steveswholesale.nz

Emergency Contact: Steve Collings

www.birchwoodcasey.com

Telephone (General) • 952-388-6717

Emergency Conta
0800 303 303

**Felephone (General)** • 952-388-6717 0000 303 303 0274 905 708

**1.4 Emergency telephone number** Poison Control 0800 POISON (0800 764

**Manufacturer** • 1-800-424-9300 - CHEMTREC 766

24 HOUR POISON CONTROL EMERGENCY NUMBER: 866-291-7152 U.S. & CANADA

### **Section 2: Hazards Identification**

### **EU/EEC**

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

### 2.1 Classification of the substance or mixture

**CLP**• Flammable Liquids 3 - H226
Aspiration 1 - H304

• Flammable Harmful (Xn)

R10, R65

2.2 Label Elements

Preparation Date: 17/Dec/2012

Revision Date: 1/Aug/2013

**CLP** 

### **DANGER**





**Hazard statements** • H226 - Flammable liquid and vapour H304 - May be fatal if swallowed and enters airways

**Precautionary statements** 

Prevention • P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground and/or bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response • P370+P378 - In case of fire: Use appropriate media for extinction.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

P331 - Do NOT induce vomiting.

**Storage/Disposal** • P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

DSD/DPD



Risk phrases • R10 - Flammable.

R65 - Harmful: may cause lung damage if swallowed.

2.3 Other Hazards

**CLP** • According to Regulation (EC) No. 1272/2008 (CLP) this material is considered

hazardous.

**DSD/DPD** • According to European Directive 1999/45/EC this material is considered dangerous.

### **United States (US)**

According to OSHA 29 CFR 1910.1200 HCS

### 2.1 Classification of the substance or mixture

**OSHA HCS 2012** 

Flammable Liquids 3 - H226
 Skin Irritation 2 - H315
 Eye Irritation 2A - H319

Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

Specific Target Organ Toxicity Repeated Exposure 2 - H373

# 2.2 Label elements

OSHA HCS 2012

#### **DANGER**







### Hazard statements . Flammable liquid and vapour - H226

Causes skin irritation - H315

Causes serious eye irritation - H319 May cause respiratory irritation - H335 May cause drowsiness or dizziness - H336

May cause damage to organs - Liver/Kidney through prolonged or repeated exposure via Unreported Route - H373

### **Precautionary statements**

**Prevention** • Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. - P210

Keep container tightly closed. - P233

Ground and/or bond container and receiving equipment. - P240

Use explosion-proof electrical/ventilating/lighting/equipment. - P241

Use only non-sparking tools. - P242

Take precautionary measures against static discharge. - P243

Do not breathe mist/vapours/spray. - P260 Wash thoroughly after handling. - P264

Use only outdoors or in a well-ventilated area. - P271

Wear protective gloves/protective clothing/eye protection/face protection. - P280

#### Response .

In case of fire: Use appropriate media for extinction. - P370+P378

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340

Call a POISON CENTER or doctor/physician if you feel unwell. - P312

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. - P303+P361+P353

Specific treatment, see supplemental first aid information. - P321 Take off contaminated clothing and wash before reuse. - P362 If skin irritation occurs: Get medical advice/attention. - P332+P313

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. - P305+P351+P338

If eye irritation persists: Get medical advice/attention. - P337+P313 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. -

P309+P311

Get medical advice/attention if you feel unwell. - P314

### Storage/Disposal .

Store in a well-ventilated place. Keep container tightly closed. - P403+P233 Keep cool. - P235

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501

Store locked up. - P405

### 2.3 Other hazards

**OSHA HCS 2012** 

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

#### Canada

According to WHMIS

#### 2.1 Classification of the substance or mixture

**WHMIS** 

Flammable Liquids - B2 Other Toxic Effects - D2B

### 2.2 Label elements

WHMIS





Flammable Liquids - B2 Other Toxic Effects - D2B

### 2.3 Other hazards

**WHMIS** 

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

### Section 3 - Composition/Information on Ingredients

#### 3.1 Substances

 Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

### 3.2 Mixtures

	Composition						
Chemical Name	al Name Identifiers % LD50/LC50 Classifications According to Regulation/Directive		Comments				
Stoddard solvent	CAS:8052-41-3 EC Number:232- 489-3	85%	Inhalation-Rat LC50 • >1400 ppm 8 Hour(s)	EU DSD/DPD: Annex I: Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65 EU CLP: Annex VI: Carc. 1B, H350; Muta. 1B, H340; Asp. Tox. 1, H304 OSHA HCS 2012: Flam. Liq. 3; Eye Irrit. 2A; Skin Irrit. 2; STOT RE 2 (Liver & Kidney); Asp. Tox. 1; STOT SE 3: Narc.	NDA		
Hydrocarbon Wax	NDA	9%	NDA	EU DSD/DPD: Data lacking EU CLP: Data lacking OSHA HCS 2012: Data lacking	NDA		
Polydimethyl Siloxane	CAS:63148-62-9 EC Number:	3%	Ingestion/Oral-Rat LD50 • >17 g/kg Skin-Rabbit LD50 • >2 g/kg	EU DSD/DPD: Not Classified - Criteria not met			
Carnauba Wax	CAS:8015-86-9 EINECS:232- 399-4	3%	NDA	EU DSD/DPD: Data lacking EU CLP: Data lacking OSHA HCS 2012: Data lacking	NDA		

See Section 11 for Toxicological Information. See Section 16 for full text of H-statements and R-phrases.

### Section 4 - First Aid Measures

### 4.1 Description of first aid measures

Inhalation

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

• In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Eye

 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

 If victim is conscious, give 1 – 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.

### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to Physician** 

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

### Section 5 - Firefighting Measures

### 5.1 Extinguishing media

Suitable Extinguishing Media . Foam, dry chemical, carbon dioxide or any Class B extinguishing agent.

Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent

Unsuitable Extinguishing

#### Media

containers cool.

### 5.2 Special hazards arising from the substance or mixture

# Unusual Fire and Explosion Hazards

Containers may explode when heated.

Vapor explosion hazard indoors, outdoors or in sewers.

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Many liquids are lighter than water.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Runoff to sewer may create fire or explosion hazard.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

# Hazardous Combustion Products

No data available

### 5.3 Advice for firefighters

Structural firefighters' protective clothing will only provide limited protection.
 Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

### Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

 Do not walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist, vapours, spray. Wear appropriate personal protective equipment, avoid direct contact. Avoid contact with skin, eyes or clothing.

#### **Emergency Procedures**

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

### 6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

### 6.3 Methods and material for containment and cleaning up

# Containment/Clean-up Measures

Stop leak if you can do it without risk.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

#### 6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

### Section 7 - Handling and Storage

### 7.1 Precautions for safe handling

### Handling

• Keep away from heat and ignition sources – No Smoking. All equipment used when handling the product must be grounded. Take precautionary measures against static charges. Do not breathe mist, vapours, spray. Use only with adequate ventilation.

Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Wear appropriate personal protective equipment, avoid direct contact. Avoid contact with skin, eyes, and clothing. Empty containers may still have product residue and flammable vapors. Avoid spontaneous combustion of contaminated rags and other easily ignitable accumulations (such as spray booth residues) by immediate immersion in water.

### 7.2 Conditions for safe storage, including any incompatibilities

### **Storage**

 Keep away from sources of ignition – No Smoking. Store in a cool, dry, well-ventilated place. Store in a tightly closed container. Do not store where temperature may exceed 120°F.

### 7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

### Section 8 - Exposure Controls/Personal Protection

### 8.1 Control parameters

Exposure Limits/Guidelines							
	Result ACGIH Canada Ontario Canada Quebec NIOSH OSHA						
Stoddard solvent	TWAs	100 ppm TWA	525 mg/m3 TWA (140°C Flash aliphatic solvent)	100 ppm TWAEV; 525 mg/m3 TWAEV	350 mg/m3 TWA	500 ppm TWA; 2900 mg/m3 TWA	
(8052-41-3)	Ceilings	Not established	Not established	Not established	1800 mg/m3 Ceiling (15 min)	Not established	

### 8.2 Exposure controls

Engineering Measures/Controls  Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

#### **Personal Protective Equipment**

Respiratory

 Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face Skin/Body Wear safety goggles.

Wear appropriate gloves.

**Environmental Exposure Controls** 

 Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

#### Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene NIOSH = National Institute of Occupational Safety and Health

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

OSHA = Occupational Safety and Health Administration

### **Section 9 - Physical and Chemical Properties**

### 9.1 Information on Physical and Chemical Properties

Material Description				
Physical Form	Liquid	Appearance/Description	Opaque, burnt orange liquid with a naphtha odor.	

Color	Burnt orange.	Odor	Naphtha
Odor Threshold	Data lacking		
General Properties			
Boiling Point	> 300 F(> 148.8889 C)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	рН	Data lacking
Specific Gravity/Relative Density	< 0.775 Water=1	Water Solubility	Negligible
Viscosity	Data lacking	Explosive Properties	Not Explosive.
Oxidizing Properties:	Not an oxidizer.		
Volatility			
Vapor Pressure	< 12 mmHg (torr)	Vapor Density	> 1 Air=1
Evaporation Rate	< 1 Ether = 1	Volatiles (Vol.)	> 88 %
Flammability	•		
Flash Point	108 F(42.2222 C) CC (Closed Cup)	UEL	6 %
LEL	1 %	Autoignition	Data lacking
Flammability (solid, gas)	Flammable Liquid.		
Environmental		-	
Octanol/Water Partition coefficient	Data lacking		

### 9.2 Other Information

No additional physical and chemical parameters noted.

### **Section 10: Stability and Reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

• Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

• Hazardous polymerization will not occur.

### 10.4 Conditions to avoid

Avoid high temperatures (>120°F) and ignition sources.

### 10.5 Incompatible materials

. Strong oxidizers.

### 10.6 Hazardous decomposition products

• Thermal decomposition may produce carbon monoxide, carbon dioxide, sulfur oxides.

# **Section 11 - Toxicological Information**

### 11.1 Information on toxicological effects

Component Name CAS		Data
Stoddard solvent (85%)	8052-41-3	Irritation: eye-rbt 500 mg/24H MOD
Polydimethyl Siloxane (3%)	63148-62-9	Acute Toxicity: orl-rat LD50:>17 gm/kg; skn-rbt LD50:>2 gm/kg; Irritation: eye-rbt 100 uL/24H MOD; skn-rbt 500 uL/24H MLD

GHS Properties	Classification		
A suita tauriaitu	EU/CLP • Classification criteria not met		
Acute toxicity	OSHA HCS 2012 • Classification criteria not met		

Aspiration Hazard	EU/CLP • Aspiration 1 OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2
STOT-SE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects;Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Eye Irritation 2A

**Target Organs** 

### Route(s) of entry/exposure Potential Health Effects Inhalation

Acute (Immediate)

**Chronic (Delayed)** 

### Skin

Acute (Immediate)

**Chronic (Delayed)** 

#### Eye

Acute (Immediate)

**Chronic (Delayed)** 

### Ingestion

Acute (Immediate)

riculo (illiniculato)

Chronic (Delayed)

### Other

Chronic (Delayed)

- Central Nervous System (CNS), Liver, Kidney
- Inhalation, Skin, Eye, Ingestion
- May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- No data available.
- Causes skin irritation.
- No data available.
- Causes serious eye irritation.
- No data available.
- Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- No data available.
- Stoddard solvent causes target organ effects to liver and kidneys in animal studies.

Key to abbreviations

LD = Lethal Dose

MLD = Mild

MOD = Moderate

### **Section 12 - Ecological Information**

### 12.1 Toxicity

Material data lacking.

### 12.2 Persistence and degradability

Material data lacking.

### 12.3 Bioaccumulative potential

Material data lacking.

### 12.4 Mobility in Soil

Material data lacking.

### 12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

### 12.6 Other adverse effects

• No studies have been found.

### **Section 13 - Disposal Considerations**

### 13.1 Waste treatment methods

**Product waste** 

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### **Section 14 - Transport Information**

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1993	Flammable liquid, n.o.s. (Naphtha, Petroleum)	3	III	NDA
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Naphtha, Petroleum)	3	III	NDA
IMO/IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Naphtha, Petroleum)	3	III	NDA
IATA/ICAO	UN1993	Flammable liquid, n.o.s. (Naphtha, Petroleum)	3	III	NDA

14.6 Special precautions for user

None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

### Section 15 - Regulatory Information

HSR002662

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications . Acute, Chronic, Fire

State Right To Know					
Component	CAS	MA	NJ	PA	
Stoddard solvent	8052-41-3	Yes	Yes	Yes	
Hydrocarbon Wax	NDA	No	No	No	
Carnauba Wax	8015-86-9	No	No	No	
Polydimethyl Siloxane	63148-62-9	No	No	No	

	Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA	
Stoddard solvent	8052-41-3	Yes	No	Yes	No	Yes	
Hydrocarbon Wax	NDA	No	No	No	No	No	
Carnauba Wax	8015-86-9	Yes	No	Yes	No	Yes	
Polydimethyl Siloxane	63148-62-9	Yes	No	No	No	Yes	

### Canada

#### Labor

#### Canada - WHMIS - Classifications of Substances

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 B3, D2B

### Canada - WHMIS - Ingredient Disclosure List

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 1 %

#### **Environment**

#### Canada - CEPA - Priority Substances List

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### **Europe**

#### -Other

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed

Stoddard solvent
 8052-41-3
 Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed

Stoddard solvent 8052-41-3 T R:45-46-65 S:53-45

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

• Polydimethyl Siloxane 63148-62-9 Not Listed

• Carnauba Wax 8015-86-9 Not Listed

Stoddard solvent 8052-41-3 F

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 S:53-45

#### Mexico

#### Other

#### **Mexico - Hazard Classifications**

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### Mexico - Regulated Substances

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### **United States**

### Labor

### U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### **U.S. - OSHA - Specifically Regulated Chemicals**

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### Environment

#### U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### **United States - California**

#### Environment<sup>-</sup>

### U.S. - California - Proposition 65 - Carcinogens List

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - California - Proposition 65 - Developmental Toxicity

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - California - Proposition 65 - Reproductive Toxicity - Female

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - California - Proposition 65 - Reproductive Toxicity - Male

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### **United States - Pennsylvania**

#### Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

#### U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

Polydimethyl Siloxane 63148-62-9 Not Listed
 Carnauba Wax 8015-86-9 Not Listed
 Stoddard solvent 8052-41-3 Not Listed

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

### **Section 16 - Other Information**

#### SW Revision 01.12.2020

#### Relevant Phrases (code & full text)

H340 - May cause genetic defects.

H350 - May cause cancer.

R45 - May cause cancer.

R46 - May cause heritable genetic damage.

Last Revision Date
Preparation Date
Disclaimer/Statement of
Liability

- 1/Aug/2013
- 17/Dec/2012
- The data here is for hazard communication to our employees, our customers and their employees, and authorized regulatory agencies. For the intended purpose, this SDS (Safety data Sheet) may be duplicated or the data transcribed to an alternative form. NOTE: The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, Birchwood Casey LLC makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular period. Accordingly, Birchwood Casey LLC will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

### Key to abbreviations

NDA = No data available