

## Safety Data Sheet



### Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

#### 1.1 Product identifier

<b>Product Name</b>	• <b>Barricade Rust Protection: liquid</b>
<b>Synonyms</b>	• Barricade(R) (formerly Sheath(R)) Rust Preventive
<b>Product Code</b>	• 33128; 33132

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

<b>Relevant identified use(s)</b>	• A moisture displacing rust protectant for firearms
-----------------------------------	--

#### 1.3 Details of the supplier of the safety data sheet

<b>Manufacturer</b>	• Birchwood Casey, LLC 7887 Fuller Road, Suite 100 Eden Prairie, MN 55344 United States www.birchwoodcasey.com	NZ DISTRIBUTOR Steve's Wholesale Ltd. Units 5 – 7 / 408 The Esplanade Island Bay Wellington 6023 team@steveswholesale.nz Emergency Contact: Steve Collings 0800 303 303 0274 905 708 Poison Control 0800 POISON (0800 764 766)
<b>Telephone (General)</b>	• 952-388-6717	
<b>1.4 Emergency telephone number</b>		
<b>Manufacturer</b>	• 1-800-424-9300 - CHEMTREC	

### Section 2: Hazards Identification

#### EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]  
According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

#### 2.1 Classification of the substance or mixture

<b>CLP</b>	• Flammable Liquids 3 - H226 Aspiration 1 - H304 Skin Irritation 2 - H315 Eye Irritation 2 - H319 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335 Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336
<b>DSD/DPD</b>	• Flammable Harmful (Xn) Irritant (Xi) R10, R36/37/38, R65, R67

#### 2.2 Label Elements

<b>CLP</b>	<b>DANGER</b>
------------	---------------



- Hazard statements**
- H226 - Flammable liquid and vapour
  - H304 - May be fatal if swallowed and enters airways
  - H315 - Causes skin irritation
  - H319 - Causes serious eye irritation
  - H335 - May cause respiratory irritation
  - H336 - May cause drowsiness or dizziness

### Precautionary statements

- Prevention**
- P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
  - P233 - Keep container tightly closed.
  - P240 - Ground and/or bond container and receiving equipment.
  - P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
  - P242 - Use only non-sparking tools.
  - P243 - Take precautionary measures against static discharge.
  - P261 - Avoid breathing mist/vapours/spray.
  - P264 - Wash thoroughly after handling.
  - P271 - Use only outdoors or in a well-ventilated area.
  - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- P370+P378 - In case of fire: Use appropriate media for extinction.
  - P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
  - P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
  - P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
  - P321 - Specific treatment, see supplemental first aid information.
  - P352 - Wash with plenty of soap and water.
  - P362 - Take off contaminated clothing and wash before reuse.
  - P332+P313 - If skin irritation occurs: Get medical advice/attention.
  - P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P337+P313 - If eye irritation persists: Get medical advice/attention.
  - P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
  - P331 - Do NOT induce vomiting.
- Storage/Disposal**
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
  - P235 - Keep cool.
  - P405 - Store locked up.
  - P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### DSD/DPD



- Risk phrases**
- R10 - Flammable.
  - R36/37/38 - Irritating to eyes, respiratory system and skin.
  - R65 - Harmful: may cause lung damage if swallowed.
  - R67 - Vapours may cause drowsiness and dizziness.
- Safety phrases**
- S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

## 2.3 Other Hazards

- CLP**
- According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

- DSD/DPD**
- According to European Directive 1999/45/EC this material is considered dangerous.

## United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

## 2.1 Classification of the substance or mixture

### OSHA HCS 2012

- Flammable Liquids 3  
Aspiration 1  
Skin Irritation 2  
Eye Irritation 2A  
Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation  
Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

## 2.2 Label elements

### OSHA HCS 2012

#### DANGER



- Hazard statements**
- Flammable liquid and vapour  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation  
May cause drowsiness or dizziness

#### Precautionary statements

- Prevention**
- Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground and/or bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing mist/vapours/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- In case of fire: Use appropriate media for extinction.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a POISON CENTER or doctor/physician if you feel unwell.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
Specific treatment, see supplemental first aid information.  
Wash with plenty of soap and water.  
Take off contaminated clothing and wash before reuse.  
If skin irritation occurs: Get medical advice/attention.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
Do NOT induce vomiting.
- Storage/Disposal**
- Store in a well-ventilated place. Keep container tightly closed.  
Keep cool.  
Store locked up.  
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## 2.3 Other hazards

### OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

## Canada

### According to: WHMIS

## 2.1 Classification of the substance or mixture

### WHMIS

- Combustible Liquids - B3
- Other Toxic Effects - D2B

## 2.2 Label elements

### WHMIS



- Combustible Liquids - B3
- Other Toxic Effects - D2B

## 2.3 Other hazards

### WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

## Section 3 - Composition/Information on Ingredients

### 3.1 Substances

- Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

### 3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Distillates (petroleum), hydrotreated light	CAS:64742-47-8 EC Number:265-149-8	60%	NDA	EU DSD/DPD: EU CLP, Annex VI, Table 3.2: Xn, R65 EU CLP: EU CLP, Annex VI, Table 3.1: Asp. Tox. 1, H304 OSHA HCS 2012: Data lacking	NDA
Heavy Petroleum Oxygenates, Barium Neutralized	NDA	20%	NDA	EU DSD/DPD: Data lacking EU CLP: Data lacking OSHA HCS 2012: Data lacking	NDA
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	CAS:64742-52-5 EC Number:265-155-0	15%	NDA	EU DSD/DPD: EU CLP, Annex VI, Table 3.2: Carc.Cat.2, R45 EU CLP: EU CLP, Annex VI, Table 3.1: Carc. 1B, H350 OSHA HCS 2012: Skin Irrit. 2	NDA
2-Propanol, 1-methoxy-	CAS:107-98-2 EC Number:203-539-1	4%	Inhalation-Rat LC50 • 10000 ppm 5 Hour(s) Skin-Rabbit LD50 • 13 g/kg Ingestion/Oral-Rat LD50 • 6600 mg/kg	EU DSD/DPD: EU CLP, Annex VI, Table 3.2: R10; R67 EU CLP: Annex VI, Table 3.1: Flam. Liq. 3, H226; STOT SE 3, H336 OSHA HCS 2012: STOT SE 3: Narc.; Eye Irrit. 2B	NDA

See Section 16 for full text of H-statements and R-phrases.

## Section 4 - First Aid Measures

## 4.1 Description of first aid measures

- Inhalation**
- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.
- Skin**
- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. If irritation develops and persists, get medical attention.
- Eye**
- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion**
- Do NOT induce vomiting. Obtain medical attention immediately if ingested.

## 4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

## 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

## Section 5 - Firefighting Measures

### 5.1 Extinguishing media

- Suitable Extinguishing Media**
- Water spray, carbon dioxide, dry chemical, foam.
- Unsuitable Extinguishing Media**
- Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

### 5.2 Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- Containers may explode when heated.  
Vapor explosion hazard indoors, outdoors or in sewers.  
HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.  
Many liquids are lighter than water.  
Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).  
Runoff to sewer may create fire or explosion hazard.  
Vapors may form explosive mixtures with air.  
Vapors may travel to source of ignition and flash back.

- Hazardous Combustion Products**
- No data available

### 5.3 Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection.  
Wear positive pressure self-contained breathing apparatus (SCBA).  
Move containers from fire area if you can do it without risk.  
LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

## Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal Precautions**
- Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Emergency Procedures**
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind

evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

**6.2 Environmental precautions**

- Prevent entry into waterways, sewers, basements or confined areas.

**6.3 Methods and material for containment and cleaning up**

**Containment/Clean-up Measures**

- Stop leak if you can do it without risk.  
Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.  
Use clean non-sparking tools to collect absorbed material.  
A vapor suppressing foam may be used to reduce vapors.  
All equipment used when handling the product must be grounded.  
LARGE SPILLS: Dike far ahead of liquid spill for later disposal.  
LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**6.4 Reference to other sections**

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

**Section 7 - Handling and Storage**

**7.1 Precautions for safe handling**

**Handling**

- Keep away from heat and ignition sources – No Smoking. All equipment used when handling the product must be grounded. Take precautionary measures against static charges. Empty containers may still have product residue and flammable vapors. Use only with adequate ventilation. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing mist, vapours, spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

- Keep away from sources of ignition – No Smoking. Store in a cool, dry, well-ventilated place. Store in a tightly closed container.

**7.3 Specific end use(s)**

- Refer to Section 1.2 - Relevant identified uses.

**Section 8 - Exposure Controls/Personal Protection**

**8.1 Control parameters**

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	Germany DFG	Germany TRGS
2-Propanol, 1-methoxy- (107-98-2)	STELs	100 ppm STEL	150 ppm STEL	150 ppm STEV; 553 mg/m3 STEV	Not established	Not established
	TWAs	50 ppm TWA	100 ppm TWA	100 ppm TWA EV; 369 mg/m3 TWA EV	Not established	100 ppm TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, exposure factor 2); 370 mg/m3 TWA AGW (The risk of damage to the embryo or fetus can be excluded when

						AGW and BGW values are observed, exposure factor 2)
	Ceilings	Not established	Not established	Not established	200 ppm Peak; 740 mg/m3 Peak	Not established
	MAKs	Not established	Not established	Not established	100 ppm TWA MAK; 370 mg/m3 TWA MAK	Not established
Distillates (petroleum), hydrotreated light (64742-47-8)	Ceilings	Not established	Not established	Not established	40 ppm Peak; 280 mg/m3 Peak	Not established
	MAKs	Not established	Not established	Not established	20 ppm TWA MAK; 140 mg/m3 TWA MAK	Not established
<b>Exposure Limits/Guidelines (Con't.)</b>						
			<b>Result</b>	<b>NIOSH</b>		
2-Propanol, 1-methoxy- (107-98-2)			STELs	150 ppm STEL; 540 mg/m3 STEL		
			TWAs	100 ppm TWA; 360 mg/m3 TWA		

**Exposure Control Notations**

**ACGIH**

•2-Propanol, 1-methoxy- (107-98-2): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen)

**Germany DFG**

•Distillates (petroleum), hydrotreated light (64742-47-8): **Carcinogens:** (Category 3B (could be carcinogenic for man, isomers in technical mixtures)) | **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to)

•2-Propanol, 1-methoxy- (107-98-2): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to)

**Exposure Limits Supplemental**

**ACGIH**

•2-Propanol, 1-methoxy- (107-98-2): **TLV Basis - Critical Effects:** (eye and upper respiratory tract irritation)

**8.2 Exposure controls**

**Engineering Measures/Controls**

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

**Personal Protective Equipment**

**Respiratory**

- Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

**Eye/Face**

- Wear safety goggles.

**Skin/Body**

- Wear appropriate gloves.

**Environmental Exposure Controls**

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

**Key to abbreviations**

ACGIH = American Conference of Governmental Industrial Hygiene

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

NIOSH = National Institute of Occupational Safety and Health

STEL = Short Term Exposure Limits are based on 15-minute exposures

OSHA = Occupational Safety and Health Administration

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

TLV = Threshold Limit Value determined by the American Conference of Governmental Industrial Hygienists (ACGIH)

## Section 9 - Physical and Chemical Properties

### 9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Brown liquid with a kerosene-like odor.
Color	Brown	Odor	Kerosene-like
Odor Threshold	Data lacking		
General Properties			
Boiling Point	> 300 F(> 148.8889 C)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	= 0.825	Water Solubility	Immiscible
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	> 1 Air=1
Evaporation Rate	< 1 Ether = 1	Volatiles (Vol.)	> 70 %
Flammability			
Flash Point	111 F(43.8889 C) CC (Closed Cup)	UEL	6 %
LEL	1 %	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

### 9.2 Other Information

- No additional physical and chemical parameters noted.

## Section 10: Stability and Reactivity

### 10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

- Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

### 10.4 Conditions to avoid

- Avoid high temperatures and ignition sources.

### 10.5 Incompatible materials

- Strong oxidizers.

### 10.6 Hazardous decomposition products

- Thermal decomposition may produce carbon monoxide, carbon dioxide, sulfur oxides, various hydrocarbons.



## Section 11 - Toxicological Information

### 11.1 Information on toxicological effects

Components		
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) (15%)	64742-52-5	<b>Irritation:</b> Skin-Rabbit • 500 mg • Severe irritation
2-Propanol, 1-methoxy- (4%)	107-98-2	<b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 6600 mg/kg; <b>Brain and Coverings:Other degenerative changes;</b> <b>Behavioral:General anesthetic;</b> <b>Lungs, Thorax, or Respiration:Dyspnea;</b> Inhalation-Rat LC50 • 10000 ppm 5 Hour(s); <b>Irritation:</b> Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation; <b>Reproductive:</b> Inhalation-Rat TCLo • 3000 ppm 6 Hour(s)(6-15D preg); <b>Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system</b>

GHS Properties	Classification
<b>Acute toxicity</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>Aspiration Hazard</b>	EU/CLP • Aspiration 1 OSHA HCS 2012 • Aspiration 1
<b>Carcinogenicity</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>Germ Cell Mutagenicity</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>Skin corrosion/Irritation</b>	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
<b>Skin sensitization</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>STOT-RE</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>STOT-SE</b>	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
<b>Toxicity for Reproduction</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>Respiratory sensitization</b>	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
<b>Serious eye damage/Irritation</b>	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2A

### Potential Health Effects

#### Inhalation

##### Acute (Immediate)

- May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

##### Chronic (Delayed)

- No data available.

#### Skin

##### Acute (Immediate)

- Causes skin irritation.

**Chronic (Delayed)**

- No data available.

**Eye****Acute (Immediate)**

- Causes serious eye irritation.

**Chronic (Delayed)**

- No data available.

**Ingestion****Acute (Immediate)**

- Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

**Chronic (Delayed)**

- No data available.

**Key to abbreviations**

LD = Lethal Dose

TC = Toxic Concentration

**Section 12 - Ecological Information****12.1 Toxicity**

- Material data lacking.

**12.2 Persistence and degradability**

- Material data lacking.

**12.3 Bioaccumulative potential**

- Material data lacking.

**12.4 Mobility in Soil**

- Material data lacking.

**12.5 Results of PBT and vPvB assessment**

- No PBT and vPvB assessment has been conducted.

**12.6 Other adverse effects**

- No studies have been found.

**Section 13 - Disposal Considerations****13.1 Waste treatment methods****Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Packaging waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Section 14 - Transport Information**

	<b>14.1 UN number</b>	<b>14.2 UN proper shipping name</b>	<b>14.3 Transport hazard class(es)</b>	<b>14.4 Packing group</b>	<b>14.5 Environmental hazards</b>
DOT	UN1993	Flammable Liquid, n.o.s. (Naphtha, Petroleum)	3	III	NDA
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Naphtha, Petroleum)	3	III	NDA

IMO/MDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Naphtha, Petroleum)	3	III	NDA
IATA/ICAO	UN1993	Flammable Liquid, n.o.s. (Naphtha, Petroleum)	3	III	NDA

**14.6 Special precautions for user** ● None known.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** ● Not relevant.

## Section 15 - Regulatory Information

HSR002662

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** ● Acute, Fire

State Right To Know				
Component	CAS	MA	NJ	PA
2-Propanol, 1-methoxy-	107-98-2	Yes	Yes	Yes
Distillates (petroleum), hydrotreated light	64742-47-8	No	No	No
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	No	No	No

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS
2-Propanol, 1-methoxy-	107-98-2	Yes	No	Yes	Yes	No
Distillates (petroleum), hydrotreated light	64742-47-8	Yes	No	Yes	Yes	No
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Yes	No	Yes	Yes	No

Inventory (Con't.)		
Component	CAS	TSCA
2-Propanol, 1-methoxy-	107-98-2	Yes
Distillates (petroleum), hydrotreated light	64742-47-8	Yes
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Yes

Refined)

**Canada****Labor****Canada - WHMIS - Classifications of Substances**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	B2

**Canada - WHMIS - Ingredient Disclosure List**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	1 %

**Environment****Canada - CEPA - Priority Substances List**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

**Other****Canada - Accelerated Reduction/Elimination of Toxics (ARET)**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

**Europe****Other****EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification**

• Distillates (petroleum), hydrotreated light	64742-47-8	Xn; R65
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Carc.Cat.2; R45
• 2-Propanol, 1-methoxy-	107-98-2	R10 R67

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling**

• Distillates (petroleum), hydrotreated light	64742-47-8	Xn R:65 S:(2)-23-24-62
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	T R:45 S:53-45
• 2-Propanol, 1-methoxy-	107-98-2	R:10-67 S:(2)

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	L
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases**

• Distillates (petroleum), hydrotreated light	64742-47-8	S:(2)-23-24-62
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	S:53-45
• 2-Propanol, 1-methoxy-	107-98-2	S:(2)

## United States

### Labor

#### U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - OSHA - Specifically Regulated Chemicals

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

### Environment

#### U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

#### U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

## United States - California

### Environment

#### U.S. - California - Proposition 65 - Carcinogens List

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed

• 2-Propanol, 1-methoxy-	107-98-2	Not Listed
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed
<b>U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed
<b>U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Male</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

## United States - Pennsylvania

### Labor

<b>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed
<b>U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances</b>		
• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	Not Listed
• 2-Propanol, 1-methoxy-	107-98-2	Not Listed

## 15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

## Section 16 - Other Information

SW Revised 01.12.2020

### Relevant Phrases (code & full text)

- H350 - May cause cancer.
- R45 - May cause cancer.

### Last Revision Date

- 05/March/2015

### Preparation Date

- 05/March/2015

### Disclaimer/Statement of Liability

- The data here is for hazard communication to our employees, our customers and their employees, and authorized regulatory agencies. For the intended purpose, this SDS

(Safety data Sheet) may be duplicated or the data transcribed to an alternative form. NOTE: The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, Birchwood Casey LLC makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular period. Accordingly, Birchwood Casey LLC will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

**Key to abbreviations**

NDA = No data available

---