BIRCHWOOD CASEY

SAFETY DATA SHEET

Page 1 of 6 **BC-015**

Prepa	ared to OSHA, ACC, ANSI, N	OHSC, WHMIS, 2	2001/58 & 1272/2	008/EC Standar	ds		SDS	Revisio	n: 1.0		SDS	Revisio	n Date:	1/2/2015
		1.	PRODUC	Т & СОМ	PANY	IDE	NTIF	FICA	TIO	Ν				
1.1	Product Name:									NZ DI	STRIB s Whol		td. Unit	s 5 – 7 / 408
1.2	Chemical Name:	Mixture									splana			
1.3	Synonyms:	40128											n 6023 sale.nz	
1.4	Trade Names:	Birchwood Ca	sey Solid Film	Lubricant; ML	Pen									Collings
1.5	Product Uses & Restrictions:	Lubricant		,							303 303		0.010	o o mingo
1.6	Distributor's Name:	Birchwood Ca	sey, LLC							0274 9	905 708	3		
1.7	Distributor's Address:	7887 Fuller R	oad, Suite #100), Eden Prairie	, MN 553	44 USA	4			Poiso	n Contr	ol 0800	POISC	N (0800 764 766)
1.8	Emergency Phone:	ChemTrec -	+1 (800) 424- <u>9</u>	9300 / +1 (70)3) 527-3	8887 o	or Pois	son C	ontro	l Cen	ter +1	(866) 291-	7152
1.9	Business Phone / Fax:	+1 (952) 388-	6717											
	2. HAZARDS IDENTIFICATION													
2.1	Hazard Identification:	This product									2110	COOL		
	2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. Classification: Flam. Liq. 2; Eye Irrit. 2; STOTSE 3 Hazard Statements (H): H225 – Highly flammable liquid and vapor. H319 – Causes serious eye irritation. H336 – May cause drowsiness or dizziness. Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. No smoking. P233 – Keep container tightly closed. P242 – Use non-sparking tools. P261 – Avoid breathing fume/vapor. P264 – Wash thoroughly after handling. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear protective clothing/ eye protection. P303 + P361 + P353 – IF ON SKIN – Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 – Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 +P313 – If eye irritation persists: Get medical advice/attention. P370 + P378 – In case of fire: Use Water, Foam, Co ₂ . Dry Chemical to extinguish, P403 + P235 – Store in a well ventilated place. Keep cool. P501 – Dispose of contents/container through licensed treatment, storage or disposal facility.													
		3. CC	OMPOSITI	ON & INC	GREDI	ENT	INF	OR						
							GIH om		EXPO NOHSC ppm	SURE L	IMITS IN	I AIR (m OSHA ppm	g/m³)	
								ES-	ES-	ES-				
CHEMI	CAL NAME(S)	CAS No. 646-06-0	RTECS No.	EINECS No. 211-463-5	% 15-20	NA	STEL NA	NF	STEL NF	PEAK NF	PEL NA	STEL NA	IDLH NA	OTHER
1,3-DI	OXOLANE	Flam. Lig. 2; F		211-403-5	15-20	INA	INA		INF	INF	ΝA	INA	INA	
		108-65-6	NA	203-603-9	15-20	NA	NA	50	274	NF	NA	NA	NA	-
METH	OXYISOPROPYLACETATE	Flam. Liq. 3; F		1200 000 0	10 20									
2-PRC	POXYPROPANOL	1569-01-3	NA	216-372-4	15-20	NA	NA	NF	NF	NF	NA	NA	NA	
		67-64-1	AL3150000	200-662-2	10-15	1800	NA	1185	2375	NF	2400	NA	2500	
ACET	UNE		Eye Irrit. 2; STOT				<u> </u>							
	BDENUM DISULFIDE	1317-33-5	QA4697000	215-263-9	10	NA	NA	NF	NF	NF	NA	NA	NA	
MOLI		Acute Tox. 4;			15.40					NE				
BISPH	IENOL A POLYMER	25036-25-3	NA	NA	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
		I												
	4. FIRST AID MEASURES													
4.1	First Aid: Ingestion: DO NOT INDUCE VOMITING. Contact Poison Control Center +1 (866) 291-7152 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the													
		risk of aspiration. <u>Eyes</u> : If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.												
			holding eyelid(s) open to ens	sure comp	lete flu	ishing.	If the	eyes					
		<u>Skin</u> :	holding eyelid(use, consult a Remove conta	s) open to ens physician or e minated clothi on worsens, co	sure comp mergency ng and wa	lete flu room ash affe	ishing. immed ected a	If the liately. areas v	eyes with so	or face ap and	beco wate	me sw r. If di	ollen d scomfo	



Page 2 of 6 **BC-015**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 1/2/2015

		4. FIRST AID MEASURES – cont'd							
4.2	Effects of Exposure:	Ingestion: If product is swallowed, may cause nausea, temporary gastrointestinal irritation. Vom Moderately irritating to the eyes. Symptoms of overexposure may include redness	0						
		watering.Skin:May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis)							
		some sensitive individuals. Inhalation: None expected.	some sensitive individuals.						
4.3	Symptoms of Overexposure:	Ingestion: Nausea, intestinal discomfort, vomiting and/or diarrhea.							
		Eves: Overexposure in eyes may cause redness, itching and watering.							
		Skin: Symptoms of skin overexposure may include redness, itching, and irritation of affe like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts individuals.							
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected area concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.	as. Addition	ally, high					
4.5	Chronic Health Effects:	None reported by the manufacturer.							
4.6	Target Organs:	Eyes, Skin							
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH		2					
		target organs (eyes). FLAMMABILITY		3					
		PHYSICAL HAZARDS		0					
		PROTECTIVE EQUIPM	ENT	В					
		EYES SKIN							
		5. FIREFIGHTING MEASURES							
5.1	Fire & Explosion Hazards:	This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO _X).	1						
5.2 5.3	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical. Use water spray to cool unopened containers.							
		Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.							
		6. ACCIDENTAL RELEASE MEASURES							
6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Equipment.	Personal F	Protective					
	For <u>small spills</u> (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maxi ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent ma and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove contaminated clothing and wash thoroughly before reuse.								
		For <u>large spills</u> ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with ine or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for and solid diking material to separate containers for proper disposal. Remove contaminated clothing	or recovery o	r disposal					
		affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewer water.							
		7. HANDLING & STORAGE INFORMATION							
7.1	Work & Hygiene Practices:	Avoid prolonged contact with this material. Avoid breathing the vapors generated by this pro ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty using this product. If necessary, use a moisturizer after washing. Do not eat, drink, or smoke	/ of soap & w	vater after					
7.2	Storage & Handling:	 product. Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatil Section 10. Do not store in damaged or unmarked containers or storage devices. Keep conta when not in use. Open slowly on a level, stable surface. Empty containers may contain residual ar therefore, empty containers should be handled with care. As a precaution against exposure to the face, this product should not be stored higher than waist level. Keep away from children at all times 	ble materials ainers secure mounts of this eyes, nose, t	s listed in ely closed s product;					
7.3	Special Precautions:	Do not store where temperatures can exceed 50 °C (122 °F). Spilled material may present a unattended. Clean all spills promptly.	slipping haz	ard if left					



Page 3 of 6 **BC-015**

	8										D0-0	10
Prepa	ared to OSHA, ACC, ANSI, N	IOHSC, WHMIS, 2001/58 & 1272/2008/E	C Stand	dards		SDS Rev	vision: 1.0		SDS Rev	vision Da	te: 1/2/2015	
		8. EXPOSURE CONT		5 8 1								
8.1	Exposure Limits:	U. LAFUSURE CONT				NOHSC	NULE		OSHA		OTHER	
	ppm (mg/m ³)		ES-									
		CHEMICAL NAME(S) METHOXYISOPROPYLACETATE	TLV	STEL	ES-TWA	ES-STEL	PEAK NF	PEL	STEL	IDLH		
		ACETONE	NA 1800	NA NA	50 1185	274 2375	NF	NA 2400	NA NA	NA 2500		
3.2	Ventilation & Engineering			1		L	1				tion fana)	Enou
	Controls:	When working with large quantitie that an eyewash station, sink or w							exhaus	st ventila	alion, lans).	Ensu
8.3	Respiratory Protection:	necessary, use only respiratory §1910.134, or applicable U.S.	special respiratory protection is required under typical circumstances of use or handling. If cessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR 010.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its									
8.4	Eye Protection:	Wear protective eyewear (e.g., product. Always use protective	rovinces, E.C. member states, or Australia. /ear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this roduct. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a									
8.5	Hand Protection:	special hazard; soft lenses may a					ring use o	f thic r	roduct	weer	-	
0.0		If anticipated that prolonged & rolatex or rubber gloves for routi §1910.138, the appropriate stand	ne indu ards of	ustrial u Canada	use. If ne a, of the E.	ecessary, C. membe	refer to U r states.	J.S. OS	SHA 29	CFR		
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.										
		9. PHYSICAL	& C	НЕМІ	CAL P	ROPE	RTIES					
9.1	Appearance:	liquid										
9.2	Odor:	Strong solvent odor										
9.3	Odor Threshold:	NA										
9.4	pH:	NA										
9.5	Melting Point/Freezing Point:	NA										
9.6	Initial Boiling Point/Boiling	NA										
9.7	Range: Flashpoint:	-20 ± 2 °C (-4 ± 2 °F) SETA Flash										
9.8	Upper/Lower Flammability	NA										
9.9	Limits: Vapor Pressure:	NA										
9.10	Vapor Density:	NA										
9.11	Relative Density:	1.186										
9.12	Solubility:	NA										
9.13	Partition Coefficient (log Pow):	NA										
9.14	Autoignition Temperature:	NA										
9.15	Decomposition Temperature:	NA										
9.16	Viscosity:	NA										
9.17	Other Information:	VOC: 5.0406 lb/g										
	1											
		10. STA	BILI	TY &	REAC	TIVITY	7					
10.1	Stability:	Relatively stable under ambient c	onditior	ns when	stored pro	operly.						
10.2	Hazardous Decomposition Products:	If exposed to extremely high ten gases (e.g., oxides of carbon & ni			oducts of t	hermal de	compositio	on may	include	e irritatin	ng vapors a	nd to
10.3	Hazardous Polymerization:	Will not occur.										
10.4	Conditions to Avoid:	Exposure or contact to extreme te	empera	tures, in	compatible	e chemical	ls, strong li	ight sou	irces, sp	oarks, fla	ame.	
10.5	Incompatible Substances:	Strong oxidizers, peroxides, stron						<u> </u>		•		
		11. TOXICO	DLOC	GICA	L INFO	RMAT	ION					
11.1	Routes of Entry:	Inhalation: YES			Absorp	otion: YES				Ingestion:	YES	
11.2	Toxicity Data:	This product has NOT been tester available for some of the compon								und in so	cientific liter	ature,
11.3	Acute Toxicity:	Moderate irritation to eyes and sk										
11.4	Chronic Toxicity:	This material may aggravate any	pre-exis	sting ski	in condition	n (e.g., der	matitis).					
11.5	Suspected Carcinogen:	No.										
11.6	Reproductive Toxicity:	This product is not reported to pro	oduce r	eproduc	tive toxicit	y in humar	าร.					
	Mutagenicity:	This product is not reported to pro	oduce n	nutagen	ic effects i	n humans.						
	Embryotoxicity:	This product is not reported to pro		1			IS.					
	Teratogenicity:	This product is not reported to car										
	Reproductive Toxicity:	This product is not reported to car	use rep	oroductiv	/e effects i	n humans.						



Page 4 of 6 **BC-015**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 1/2/2015

		11. TOXICOLOGICAL INFORMATION – cont'd
11.7	Irritancy of Product:	The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.
11.8	Biological Exposure Indices:	NE
1.9	Physician Recommendations:	Treat symptomatically.
		12. ECOLOGICAL INFORMATION
2.1	Environmental Stability:	There is no specific data available for this product.
2.2	Effects on Plants & Animals:	There are no specific data available for this product.
2.3	Effects on Aquatic Life:	This material should be kept out of sewage and drainage systems and all bodies of water. Releases of large volumes this product are expected to be harmful or fatal to overexposed aquatic life.
		13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)
	•	
		14. TRANSPORTATION INFORMATION
The	basic description (ID Nur	nber, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Addition
	riptive information may b	e required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.
14.1	49 CFR (GND):	UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY - IP VOL ≤ 5.0 L); or
		CONSUMER COMMODITY, ORM-D – until 01/01/2021
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL \leq 0.5 L); or
		UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY - IP VOL ≤ 1.0 L)
14.3	IMDG (OCN):	UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY - IP VOL ≤ 5.0 L)
14.4	TDGR (Canadian GND):	UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY - IP VOL ≤ 1.0 L); or
		"LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L)
14.5	ADR/RID (EU):	"LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY - IP VOL ≤ 1.0 L) UN1263, PINTURA MATERIAL RELACIONADO, 3, II (CANTIDAD LIMITADA - IP VOL ≤ 1.0 L)
14.6	SCT (MEXICO):	UN1263, PINTURA MATERIAL RELACIONADO, 3, II (CANTIDAD LIMITADA - IP VOL ≤ 1.0 L)
14.7	ADGR (AUS):	UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (IP VOL ≤ 1.0 L)
		15. REGULATORY INFORMATION HSR002603
15.1	SARA Reporting	
	Requirements:	This product does not contain any chemicals subject to the SARA Title III, section 313 reporting requirements.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity	Acetone: 2270 kg (5000 lbs)
15.5	(RQ): Other Federal Requirements:	NA
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains
0.0		all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.
15.7	State Regulatory Information:	Acetone is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware A Quality Management List (DE), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances L (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know L (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following stat criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substance List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardou Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvar Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).



Page 5 of 6 BC-015

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 1/2/2015 15. REGULATORY INFORMATION - cont'd 15.8 Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: 1,3-Dioxolane: Flammable (F) Risk Phrases (R): 11 - Extremely flammable. Safety Phrases (S): 2-16 - Keep out of reach of children. Keep away from sources of ignition - No smoking. Methoxyisopropyl Acetate: Flammable (F) Risk Phrases (R): 10 - Flammable. Safety Phrases (S): 2 - Keep out of reach of children. Acetone: Highly Flammable (F+). Risk Phrases (R): 11-36-66-67 - Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. Safety Phrases (S): 9-16-23-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Take precautionary measures against static discharges. SW revised 11.01.2021 **16. OTHER INFORMATION** 16.1 Other Information: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. Use only as directed. Keep out of reach of children. Wear suitable protective clothing. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). If skin irritation occurs: get medical advice/attention. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Birchwood Casey's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: **Birchwood Casey, LLC** 7887 Fuller Road, Suite #100 BIRCHWOOD Eden Prairie, MN 55344 USA Tel: +1 (952) 388-6701 Fax: +1 (952) 388/6702 http://www.birchwoodCasey.com 16.5 Prepared by: ShipMate. Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA ShipMate Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 Training & Consulti http://www.shipmate.com



Page 6 of 6 BC-015

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 1/2/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists					
C	Ceiling Limit					
ES Exposure Standard (Australia)						
IDLH	Immediately Dangerous to Life and Health					
OSHA	U.S. Occupational Safety and Health Administration					
PEL	Permissible Exposure Limit					
STEL	Short-Term Exposure Limit					
TLV	Threshold Limit Value					
TWA	Time Weighted Average					

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:

Α	0		G						
в	0		Н			品	3		
С	0		I						
D	B		J	0		Ŵ	3		
Е	0		κ				3		
F	0		X	Consult y special h			r SOPs foi s.		
Safety Glasses Splash Goggles Face Shield & Glove						Glove	s		
	Boots	Synthetic Apron	Protective Clothing & Full Suit						
						Î			
Full I	Face Respire	rator Dust & Vapor Half- Mask Respirator	-	ull Face spirator	Ai	irline Hoo or SCI			
ОТН	ER STAN	DARD ABBREVIATIONS	S :						
	ML Maximum Limit								
	mg/m3 milligrams per cubic meter								
	NA Not Available								
ND Not Determined									
	NE Not Established								
	NF Not Found								
	NR	No Results							
	ppm	parts per million							
L	SCBA	Self-Contained Breathing A							
NAT	NATIONAL FIRE PROTECTION ASSOCIATION: NFPA								

FI AMMABILITY LIMITS IN AIR:

FLAWIWADILI						
Autoignition	Minimum temperature required to initiate combustion in air with no other					
Temperature	source of ignition					
LEL	LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
explode or ignite in the presence of an ignition source						

HAZARD RATINGS: 0 Minimal Hazard1 Slight Hazard2 Moderate Hazard 3 Severe Hazard 4 Extreme Hazard ACD Acidic ACD Actorc ALK Alkaline COR Corrosive W Use No Water OX Oxidizer TREFOIL Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

REGOLAIC	REGULATORT IN ORMATION.						
WHMIS	Canadian Workplace Hazardous Material Information System						
DOT	U.S. Department of Transportation						
TC	Transport Canada						
EPA	U.S. Environmental Protection Agency						
DSL	Canadian Domestic Substance List						
NOHSC	National Occupational Health and Safety Commission (Australia)						
NDSL	Canadian Non-Domestic Substance List						
PSL	Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act						
EU	European Union (European Union Directive 67/548/EEC)						
WGK	Wassergefährdungsklassen (German Water Hazard Class)						
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System						

L WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

	WORKE EACE TRACK TO BE WITH TO ATTOM (WITHING) STOTEM.										
\oslash	۲		$\textcircled{\begin{subarray}{c} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	(7	۲		Ĩ				
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F				
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive				

EC (67/548/EEC) INFORMATION:

T.		N	¥2	8	® X	×	×
С	E	F	Ν	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		٩	\diamondsuit			\:		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment