

Extruded Rifle Powders

SAFETY DATA SHEET

June 2017

The following smokeless powders are distributed by Hodgdon Powder Company.

H4227[®] (NO 1.4C)

H4895[®] (EX-2015110873)

H4198® *(EX-2013031308)*

Varget® (EX-2015110873)

H4350[®] *(EX-2015110873)*

H50BMG[®] (EX-2012010785)

H4831[®] *(EX-2015110873)*

H4831SC[®] (EX-2015110873)

H1000[®] (EX-2015110873)

Retumbo® *(EX-2015110873)*

H322[®] *(EX-2016090002)*

Benchmark® (EX-2016090003)

1.4C EX Approvals in bold parenthesis

Propellant AR2209

Thales (Thales Australia Limited)

Chemwatch: **4693-51** Version No: **6.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 07/05/2013 Print Date: 05/03/2015 Initial Date: Not Available S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Propellant AR2209	NZ DISTRIBUTOR
Synonyms	Not Available	Steve's Wholesale Ltd. Units 5 – 7 / 408 The Esplanade
Proper shipping name	POWDER, SMOKELESS†	Island Bay Wellington 6023
Other means of identification	Not Available	team@steveswholesale.nz Emergency Contact: Steve Collings
Relevant identified uses of the substance or mixture and uses advised against		0800 303 303 0274 905 708
Relevant identified uses	Propellant for use in centrefire small arms ammunition.	Poison Control 0800 POISON (0800 764
		766)

Details of the manufacturer/importer

Registered company name	Thales (Thales Australia Limited)	Thales (Thales Australia Limited)
Address	Private Bag 1 Mulwala 2647 NSW Australia	Bayly Street Mulwala 2647 NSW Australia
Telephone	Not Available	+61 3 5742 2200
Fax	Not Available	+61 3 5744 1873
Website	Not Available	Not Available
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	Not Available	Thales Australia Mulwala Facility
Emergency telephone numbers	Not Available	03 5742 2200
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	3		
Toxicity	2		0 = Minimum
Body Contact	2		1 = Low 2 = Moderate
Reactivity	4		3 = High
Chronic	3		4 = Extreme

Poisons Schedule	Not Applicable
GHS Classification ^[1]	Explosive Division 1.3, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Germ Cell Mutagen Category 2, Carcinogen Category 1B, Reproductive Toxicity Category 2, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements







SIGNAL WORD DANGER

Hazard statement(s)

H203	Explosive; fire, blast or projection hazard	
H302	Harmful if swallowed	
H312	Harmful in contact with skin	

Chemwatch: **4693-51**Version No: **6.1.1.1**

Page 2 of 8

Propellant AR2209

Issue Date: **07/05/2013**Print Date: **05/03/2015**

H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H412	Harmful to aquatic life with long lasting effects
Precautionary statement(s) Prevention	

P201	Obtain special instructions before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P230	Keep wetted with phlegmatizer	
P271	Use only outdoors or in a well-ventilated area.	

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
P370+P380	In case of fire: Evacuate area.
P372	Explosion risk in case of fire.
P373	DO NOT fight fire when fire reaches explosives.

Precautionary statement(s) Storage

P405	Store locked up.
P401	Store according to local regulations for explosives

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9004-70-0	>=85	nitrocellulose
121-14-2	<10	2,4-dinitrotoluene
Not Available	<10	additives nonhazardous

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Description of first aid file	asuies
Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If furnes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

DANGER: Deliver media remotely.

- For minor fires: Flooding quantities only.
- For large fires: Do not attempt to extinguish

Special hazards arising from the substrate or mixture

Fire Incompatibility

- Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials.
- Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.

Advice for firefighters

Fire Fighting

WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!

- ▶ Evacuate all personnel and move upwind.
- Prevent re-entry.
- Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be explosively reactive, detonate and release much heat

Fire/Explosion Hazard

WARNING: HIGH EXPLOSION HAZARD! Combustible.

- Will burn with rapidly increasing intensity of fire.
- Dry material is extremely sensitive to shock, friction, heat and sparks.
- Avoid metal to metal contact.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

Clean up all spills immediately.

Avoid contact with skin and eyes. Wear impervious gloves and safety glasses

Use spark-free tools when handling Remove all ignition sources.

Major Spills

Clear area of personnel

Restrict access to area.

Alert Fire Brigade and tell them location and nature of hazard.

May be violently or explosively reactive.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this MSDS.

Avoid all personal contact, including inhalation Wear protective clothing when risk of exposure occurs.

▶ Avoid smoking, naked lights, heat or ignition sources

Must not be struck by metal implements.

Other information

Store in original containers

No smoking, naked lights, heat or ignition sources.

Keep dry.

▶ Keep storage area free of debris, waste and combustibles.

Conditions for safe storage, including any incompatibilities

Suitable container

Check containers are clearly labelled.

▶ Packaging as recommended by manufacturer. Explosives Code Packing Instruction P114(b) or 114(b)

General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met.

For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required.

Segregate from strong acids

Storage incompatibility

strong alkalis and

strong oxidisers

Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials.

Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.
















- 0 - May be stored together with specific preventions
- May be stored together

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nitrocellulose	Fume (thermally generated) (respirable dust)(g)	2 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
nitrocellulose	Pyroxylin; (Cellulose tetranitrate)	15 mg/m3	170 mg/m3	990 mg/m3
2,4-dinitrotoluene	Dinitrotoluene, 2,4-	0.6 mg/m3	4.9 mg/m3	200 mg/m3

Ingredient	Original IDLH	Revised IDLH
nitrocellulose	Not Available	Not Available
2,4-dinitrotoluene	200 mg/m3	50 mg/m3
additives nonhazardous	Not Available	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection











Eye and face protection

- Safety glasses with side shields.
- Chemical goggles
- ► Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

Hands/feet protection

Wear protective gloves, e.g. PVC.

Protective footwear

Body protection

See Other protection below

Eyewash unit.

Other protection

Ensure ready access to a burns first aid kit

▶ Impervious apron

Ensure there is ready access to a safety shower

Barrier cream

Thermal hazards

Not Available

Overalls

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Propellant AR2209

Material	СРІ
SARANEX-23	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

^{* -} Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Propellant AR2209

Page 5 of 8 Issue Date: 07/05/2013 Version No: **6.1.1.1** Print Date: 05/03/2015

Information on basic physical and chemical properties

Appearance	Dark grey tubules.		
Physical state	Divided Solid	Relative density (Water = 1)	> 1 approx
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	170
pH (as supplied)	Not Applicable	Decomposition temperature	Explosive.
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Product is considered stable under normal handling conditions. Stable under normal storage conditions. Hazardous polymerization will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

mormation on toxicologic	ar critotis		
Inhaled	Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful. The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts, or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. The decomposition vapours are harmful if inhaled in large volume.		
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia). Symptoms include cyanosis (a bluish discolouration skin and mucous membranes) and breathing difficulties.		
Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.		
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.		
Chronic	The principal hazard is related to the potential of fire/explosion and associated physical injury and toxic furne inhalation. Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.		
Propellant AR2209	TOXICITY	IRRITATION	
1 Topoliani ANEEGO	Not Available	Not Available	
nitrocellulose	TOXICITY	IRRITATION	
nitroceilulose	Oral (rat) LD50: >5000 mg/kg ^[2]	Not Available	
0.4 15 15 15 15 15 15 15 15 15 15 15 15 15	TOXICITY	IRRITATION	
2,4-dinitrotoluene	dermal (guinea pig) LD50: >1000 mg/kg ^[2]	Skin (rabbit): 500 mg/24h - mild	

Issue Date: 07/05/2013 Print Date: 05/03/2015

		I	
	Oral (rat) LD50: 268 mg/kgd ^[2]		
Legend:	Value obtained from Europe ECHA Registered Substances extracted from RTECS - Register of Toxic Effect of chemical		rom manufacturer's msds Unless otherwise specified data
NITROCELLULOSE	No significant acute toxicological data identified in literatur	e search.	
2,4-DINITROTOLUENE	for dinitrotoluene (syn: dinitromethylbenzene; DNT) In humans, heavy DNT exposure causes signs of methaem in liver function and exposure-dependent nephrotoxic effect studies without reliable exposure data and/or only small nu urothelial cancer in occupationally DNT exposed workers d pointing to an increased risk of ischemic heart disease or to studies In humans dinitrotoluene (DNT, technical grade) is absorbe	s directed to the tubular system were mbers of significantly exposed worke to not permit a conclusion on the car an adverse effect on the human mai	ers indicating increased incidences of hepatobiliary or cinogenicity of DNT in humans. Preliminary observations le reproductive system could not be confirmed by further
Acute Toxicity	~	Carcinogenicity	~
Skin Irritation/Corrosion	0	Reproductivity	✓
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	~	Aspiration Hazard	0
		l egend:	Data required to make classification available

Legend:

– Data required to make classification available

🗶 – Data available but does not fill the criteria for classification

Data Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2,4-dinitrotoluene	HIGH (Half-life = 360 days)	MEDIUM (Half-life = 118.33 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
2,4-dinitrotoluene	HIGH (BCF = 2507)

Mobility in soil

Ingredient	Mobility
2,4-dinitrotoluene	LOW (KOC = 363.8)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- Explosives must not be thrown away, buried, discarded or placed with garbage.
- Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be
- This material may be disposed of by burning or detonation but the operation may only be performed under the control of a person trained in the safe destruction of explosives.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

Not Applicable

Land transport (ADG)

UN number

Chemwatch: 4693-51 Page 7 of 8 Issue Date: 07/05/2013 Version No: 6.1.1.1 Print Date: 05/03/2015

Propellant AR2209

Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS†
Environmental hazard	No relevant data
Transport hazard class(es)	Class 1.3C Subrisk Not Applicable
Special precautions for user	Special provisions Not Applicable Limited quantity 0

Air transport (ICAO-IATA / DGR)

ii transport (ICAO-IAIA / L	•	
UN number	0161	
Packing group	Not Applicable	
UN proper shipping name	Powder, smokeless †	
Environmental hazard	No relevant data	
Transport hazard class(es)	ICAO/IATA Class 1.3C ICAO / IATA Subrisk Not Applicable ERG Code 1L	
Special precautions for user	Special provisions	Not Applicable
	Cargo Only Packing Instructions	Forbidden
	Cargo Only Maximum Qty / Pack	Forbidden
	Passenger and Cargo Packing Instructions	Forbidden
	Passenger and Cargo Maximum Qty / Pack	Forbidden
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS
Environmental hazard	Not Applicable
Transport hazard class(es)	IMDG Class 1.3C IMDG Subrisk Not Applicable
Special precautions for user	EMS Number F-B , S-Y Special provisions Not Applicable Limited Quantities 0

SECTION 15 REGULATORY INFORMATION

HSR100163

Safety, health and environmental regulations / legislation specific for the substance or mixture

nitrocellulose(9004-70-0) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs","International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft","Australia Hazardous Substances Information System - Consolidated Lists"
2,4-dinitrotoluene(121-14-2) is found on the following regulatory lists	"International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"

SECTION 16 OTHER INFORMATION

SW Revision Date 01.12.2020

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Notes

When the propellant is packed as in packgaing UN4GY12.5/S/**/AUS/ABBE 30818 it is suitable for air transport as follows: Air Transport IATA:

ICAO/IATA Class 1.4C ICAO/IATA Subrisk: None

Chemwatch: 4693-51 Page 8 of 8 Version No: 6.1.1.1

Propellant AR2209

Issue Date: 07/05/2013 Print Date: 05/03/2015

UN/ID Number: 0509 Packing Group:-

Special Provisions: None

Cargo Only

Packing Instructions: 114 Maximum Qty/Pack: 10kg

Passenger and Cargo
Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

Passenger and Cargo Limited Quantity

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.